

# KIRSCHNER WIRES

LENGTH	POINT STYLE	WIRE DIAMETER																					
		0.7mm	0.8mm	0.9mm	1.0mm	1.1mm	1.2mm	1.4mm	1.6mm	2.0mm	2.4mm	2.5mm	2.8mm										
<b>MM</b>	<b>INCH</b>																						
100	4 Trocar/Trocar	200-410-A	200-410-B	200-410-C	200-410-D	200-410-E	200-410-F	200-410-G															
100	4 Trocar/Blunt	200-411-A	200-411-B	200-411-C	200-411-D	200-411-E	200-411-F	200-411-G															
100	4 Diamond/Diamond	200-420-A	200-420-B	200-420-C	200-420-D	200-420-E	200-420-F	200-420-G															
100	4 Diamond/Drill Shank	200-425-A	200-425-B	200-425-C	200-425-D	200-425-E	200-425-F	200-425-G															
150	6 Trocar/Trocar	200-610-A	200-610-B	200-610-C	200-610-D	200-610-E	200-610-F	200-610-G	200-610-H	200-610-I	200-610-J	200-610-K											
150	6 Trocar/Blunt	200-611-A	200-611-B	200-611-C	200-611-D	200-611-E	200-611-F	200-611-G	200-611-H	200-611-I	200-611-J	200-611-K											
150	6 Diamond/Diamond	200-620-A	200-620-B	200-620-C	200-620-D	200-620-E	200-620-F	200-620-G	200-620-H	200-620-I	200-620-J	200-620-K											
150	6 Diamond/Drill Shank	200-625-A	200-625-B	200-625-C	200-625-D	200-625-E	200-625-F	200-625-G	200-625-H	200-625-I	200-625-J	200-625-K											
230	9 Trocar/Trocar			200-910-C	200-910-D	200-910-E	200-910-F	200-910-G	200-910-H	200-910-I	200-910-J	200-910-K											
230	9 Trocar/Blunt			200-911-C	200-911-D	200-911-E	200-911-F	200-911-G	200-911-H	200-911-I	200-911-J	200-911-K											
230	9 Trocar/3 Sided Shank			200-915-C	200-915-D	200-915-E	200-915-F	200-915-G	200-915-H	200-915-I	200-915-J	200-915-K											

# STEINMANN PINS

LENGTH	POINT STYLE	PIN DIAMETER						
		3.0mm	3.2mm	3.5mm	4.0mm	4.5mm	5.0mm	
<b>MM</b>	<b>INCH</b>							
230	9 Trocar/Trocar	200-950-L	200-950-M	200-950-N	200-950-O	200-950-P	200-950-Q	
230	9 Trocar/3 Sided Shank	200-955-L	200-955-M	200-955-N	200-955-O	200-955-P	200-955-Q	
230	9 Diamond/Diamond	200-960-L	200-960-M	200-960-N	200-960-O	200-960-P	200-960-Q	
230	9 Diamond/Drill Shank	200-965-L	200-965-M	200-965-N	200-965-O	200-965-P	200-965-Q	

- Surgical Implant Grade Stainless Steel to ASTM F138/ISO 5832-1
- Packed in see-through packs of 10
- Non-Sterile
- Other styles and sizes on request
- Wires and pins available in bulk
- Threaded wires available ≥ 1.6mm Diameter
- Pins passivated to ASTM F86

# ILYZAROV WIRES (without olive)

LENGTH	POINT STYLE	WIRE DIAMETER	
		1.8mm	2.00mm
<b>MM</b>	<b>INCH</b>		
370	14.5 Single D Point	200-370-X	200-370-Y

